HIGH LIFT TRUCK HE-S12/3

- High working efficiency due to 2.2 kW lift pump
- Very small steering radius of 1452 mm and large field of vision due to lateral steering drawbar
- · Four-colour LED power meter makes it easy to read the energy level
- Internal charger allows easy charging at any standard 230 V socket
- Fast transport and lifting due to the pure electric controller
- Long-life maintenance-free 24 V lead-gel battery

TECHNICAL DATA

Туре	Unit	Value
Brand		SolidHub
Model		HE-12/3
Rated Traction Weight	kg	1200
Load Center	mm	600
Min. Lifting Height	mm	80
Max. Lifting Height	mm	3000
Capacity at max. Lifting Height	kg	1200
Net Weight with Battery	kg	601
Wheelbase	mm	1300
Controller		CURTIS

DIMENSIONS

Туре	Unit	Value
Height of Mast, lowered	mm	2200
Height of Mast, extended	mm	3880
Overall Length	mm	1850
Axle Center to Forkface	mm	670
Overall Width	mm	1130 - 1450
Track Width	mm	970 - 1270
Fork Width	mm	100
Fork Length	mm	1190
Fork Height	mm	40
Outer Width of Fork	mm	750
Distance between Fork Arms	mm	1110
Battery Dimensions	mm	262 x 172 x 170
Min. Ground Clearance	mm	40
Aisle Width with Pallet 1000 mm x 1200 mm across Forks	mm	2220
Aisle Width with Pallet 800 mm x 1200 mm along Forks	mm	2295
Min. Turning Radius	mm	1700

POWER

Туре	Unit	Value
Travel Speed, loaded / unloaded	km/h	4.5 / 4.7
Lifting Speed, loaded / unloaded	mm/s	115 / 160
Lowering Speed, loaded / unloaded	mm/s	170 / 130
Max. Gradeability, loaded / unloaded	%	5/7
Service Break		Electromagnetic

ENGINE

Туре	Unit	Value
Drive Engine	kW	0.75
Lift Engine	kW	2.2
Rated Voltage	V	24
Rated Capacity	Ah	75





